



## **Autocross Tech Inspection Sheet**

NAME:					CLASS:			MEN'S	LADIES'
YEAR	/MOD	EL:	:		CAR C	OLOR:	CAR#:_		
Pass	Fail			!!! ENTRANT SHOUL AUTOMOBILE T					ING
		1.	HELM	ET - SNELL SA or M 2000 or la		shield required for	cars without win	dshields.	
		_		Snell SA or M sticker must be					
		2.		REL - Full-length pants, long sleev				-l-:	.:4-
				re feet, sandals, and open toed sh ng gloves and shoes (cotton, wool					JITS,
		3		BELTS/HARNESSES –Must be p					helts
		٥.		Where installation is other than fac					
				with large diameter washers on bo					
				used in an open vehicle only if the					
		4.		BARS/CAGES - Recommended					
				ll Bars are <b>required</b> in <b>open vehic</b>					ipped with
		_		equate padding. Roll Bars/Cages,			ւ Club Racing Rւ	ıles.	$\backslash\!\!\!\backslash$
		5.	PEDA	LS - Free return and in good opera	ating condition. Firm	brake pedal.	. // //		\\
		6.	LOOS	E OBJECTS - Remove all loose it	tems from trunk and	interior, including of	love compartme	nt, door p	ockets,
		7	COL	nsole, etc. Spare secured properly SHIELDS/WINDOWS - No major o	r (spare adds to the s	structure or certain	Porsches).		
		١.		iver and Passenger windows mus			loveu.	- ]] ,	//
				ontestants must use a face shield			in any class.		/
		8.	REMO	VEABLE ROOF PANELS/CONV	ERTBILE TOPS/SU	NROOFS- Any aut	omobile may run	with their	top down
				movable roof panels must be remo					
			full	y closed. Sliding Sunroofs may be	open.				
				AP - Gasket intact and cap tighte					
		10	RUST	-No rust or damage to suspensio	n or chassis parts th	at affect the integri	ty of the chassis	or brakes	
		11		RING and SUSPENSION - No exc					
				e and shock bolt tight. Ball joints in			boots and oil se	ais in goo	a conditioi
		12		eck half-shaft bolts and shock bolt ER – (356 automobiles) No positive					
				L/BEARINGS - Correct adjustmen			no damaged o	r hurnt he	arings
		14	BRAK	ES – Must be tested for pedal "fac	de" while vehicle is s	tationary.	i, no damaged o	i baille bo	ariiigo.
				ke linings/pads should be 4mm th			brakes.		
		15	.WHEE	LS - No cracks. No bends. All lug	nuts must be torque	ed to manufacturer'	s specifications,		one
				meter of engagement. Snap-on wl					
		16		- Must be free of visible sidewall		between tires and a	any potential rubl	bing point	
		47		st fall into compliance of chosen c					
				<b>E FLUID</b> - Level up, must show in <b>ERY (IES)</b> - Securely fastened and		No acid leaks or or	orrosion Chack	fual linas ı	ınder
		10		tery trays on 914's. The Positive (					iliuei
		19		<b>UST</b> – Must be in safe condition, r			worda by dap or	tapo.	
				BACKS – Must be suitably secure					
		21	LEAK	S - No exhaust leaks or fluid leaks	of any kind Oil, g	as, brake, or coolar	nt.		
				TTLE RETURN - Freely operating		n cars so equipped	1.		
		23	. HOOE	O AND DECK LIDS-Must fasten se	ecurely.				
		5							
/	D A	*	4	DRIVER'S SIGNATURE:				DATE:	
10		····		WITNESS TO DRIVER'S SIGNA	TUDE (Inspector):				
1				WITHESS TO DRIVER'S SIGNA	TONE (mapeolor).				
*	Y		I O F	SERVICE STAMP		_ DATE:			
		-4	1/2	/					